

CARPET TILE

AVENUE | BRIDGE | PARK



POLYPROPYLENE







GOODFLOOR

2019 - 2022.12

URBAN AVENUE

SPECIFICATIONS

COLLECTION NAME : URBAN AVENUE SQ

YARN : 100% PP

CONSTRUCTION : Tuffed Multi-Level Loop

DYE METHOD : Solution Dyed

GAUGE : 1/12" STITCHES PER INCH : 10

PILE HEIGHT : 4 mm (+/- 0.5 mm) TOTAL HEIGHT : 7 mm (+/- 0.5 mm) PILE WEIGHT : 20 oz/sy (680 gm/sm)

TOTAL WEIGHT : 178 oz/sy (4000 gm/sm +/- 200 gm/sm)

PRIMARY BACKING : Non-woven

SECONDARY BACKING: Green Backing - PVC Free

SIZE : 25 x 100 cm/tile PACKING : 20 pcs (5 sm)/box

* As with all dyed products, colours are subject to dye lot variations.

PERFORMANCE SPECIFICATIONS

COLOURFASTNESS : Grade >=4 (AATCC Test Method)


: Result: 6 = OK

FLAMMABILITY : Passed (ASTM E648, GB 8624-2006)

SMOKE DENSITY : Passed (ASTM E662, GB/T 8627-1999)

STATIC PROPENSITY : ≤ 3.0 kV (AATCC-134, GB/T 18044-2000)

RECOMMENDED INSTALLATION METHODS:







Herringbone

Ashlar

Brick



UV05 GREY



UV11 BLUE



UV12 BLACK



UV14 BEIGE



URBAN BRIDGE

SPECIFICATIONS

: URBAN BRIDGE SQ COLLECTION NAME

YARN : 100% PP

CONSTRUCTION : Tufted Level Loop DYE METHOD : Solution Dyed

GAUGE : 1/12" STITCHES PER INCH : 10

PILE HEIGHT : 4 mm (+/- 0.5 mm) TOTAL HEIGHT $: 6.5 \, \text{mm} \, (+/-0.5 \, \text{mm})$ PILE WEIGHT : 20 oz/sy (680 gm/sm)

TOTAL WEIGHT : 142 oz/sy (4800 gm/sm +/- 200 gm/sm)

PRIMARY BACKING : Non-woven

SECONDARY BACKING: PVC with fiberglass SIZE : 50 x 50 cm/tile **PACKING** : 20 pcs (5 sm)/box

* As with all dyed products, colours are subject to dye lot variations.

PERFORMANCE SPECIFICATIONS

: Grade >=4 (AATCC Test Method) COLOURFASTNESS

: Result: 6 = OK

FLAMMABILITY : Passed (ASTM E648, GB 8624-2006) SMOKE DENSITY : Passed (ASTM E662, GB/T 8627-1999) STATIC PROPENSITY $\leq 3.0 \text{ kV (AATCC-134, GB/T 18044-2000)}$


RECOMMENDED INSTALLATION METHODS:




¼ Turn



Monolithic



Brick



Ashlar



UV01 DARK GREY



UB02 GREY



UB03 BEIGE



UB04 EARTH



Collection

URBAN PARK

SPECIFICATIONS

COLLECTION NAME : URBAN PARK SQ

YARN : 100% PP

CONSTRUCTION : Tufted Multi-Level Loop

DYE METHOD : Solution Dyed

: 1/12" GAUGE STITCHES PER INCH : 10

PILE HEIGHT : 4 mm (+/- 0.5 mm) TOTAL HEIGHT : 6.5 mm (+/- 0.5 mm) PILE WEIGHT : 21 oz/sy (714 gm/sm)

TOTAL WEIGHT : 130 oz/sy (4500 gm/sm +/- 200 gm/sm)

PRIMARY BACKING : Non-woven

SECONDARY BACKING: Green Backing - PVC Free

SIZE : 25 x 100 cm/tile **PACKING** : 20 pcs (5 sm)/box

* As with all dyed products, colours are subject to dye lot variations.


PERFORMANCE SPECIFICATIONS

: Grade >=4 (AATCC Test Method) COLOURFASTNESS

: Result: 6 = OK

FLAMMABILITY : Passed (ASTM E648, GB 8624-2006) SMOKE DENSITY : Passed (ASTM E662, GB/T 8627-1999) STATIC PROPENSITY : ≤ 3.0 kV (AATCC-134, GB/T 18044-2000)

RECOMMENDED INSTALLATION METHODS:







Brick





UP01 DARK GREY



UP02 GREY



UP03 BEIGE



UP04 BLUE





GOODRICH SOLUTIONS

CARPET TILE

AVENUE | BRIDGE | PARK

WITH GOODRICH,

Your habitat becomes

A gallery of

Your self-expressions;

A canvas for Your creativity;

A space for

Your **SOUI**;

A showcase of

Your taste for life;



Stay Connected - www.goodrichglobal.com | info@goodrichglobal.com















